Thread: https://www.g8board.com/forums/42-canada/277833-need-new-rotors-pads-current-ones-warped.html#post3629506

Pertinent posts from the thread above:

#7 https://www.g8board.com/forums/3624953-post7.html
#10 https://www.g8board.com/forums/3625585-post10.html
#16 https://www.g8board.com/forums/3626129-post16.html
#18 https://www.g8board.com/forums/3629506-post18.html (with photos)

To recap, standard G8 GT uses 321mm front rotors with a twin-piston floating aluminum caliper. A popular mod has been to use the Brembo 4-piston fixed caliper and 355x32 rotor found on Gen5 Camaro SS, SS sedan, etc. Different wheels than production G8 18x8 or 19x8 are typically required to work with this brake setup.

The Caprice PPV, with the same Zeta sedan suspension as G8 & SS sedan, is fitted with a 345x30 rotor, and a single-piston floating caliper that is common with Gen5 Camaro V6. As addressed in the thread/posts above, there is now the possibility of a "hybrid" combination of Zeta & Alpha brake components to add 345mm rotors & Brembo calipers to any G8 with "small" front brakes, *and continue to use the stock 18*" *or 19*" *(non-GXP) wheels.*

While not offering the same effect as going to the 355mm or even 370mm/6-piston front setup, the change to the 345mm rotor ultimately provides at least 90% of the improvement of the larger brake options, and will quite effectively out-perform the stock 321mm brakes.

All components bolt-on:

(L/R)Calipers - Cadillac J56 for 2014-2016 CTS - specifically PN 84089036 & 84133555 (new from GM Parts Direct at \$148 each, no core charge)

(2)Rotors - 2011-2017 Caprice PPV 345mm - many sources/styles available

(1)Pads - FMSI D1474 or D1001 (addressed in thread/posts above)

(2)Pin kit - GM 22813180 (or equivalent)

(4)Bolts for mounting calipers - M14x2.0 - GM 11570092 (must drill mounting bolt holes for spindles - now 12mm)

(A/R)Hoses - stock hose may work, or custom hose









More Information for ACDELCO 1711141

Add to Cart >



Continue Shopping

Point to Zoom RockAuto.com

Pads & Shoes are sold as sets. Quantity of one (1) is for both wheels

GM Original Equipment

When you need high-quality stopping power for your vehicle, rely on ACDelco GM Original Equipment Brake Pads. Built to meet stringent FMVSS guidelines, ACDelco GM OE Brake Pads come with premium hardware, shims, chamfers, slots and are integrally-molded (I-M) for excellent heat characteristics and long-life performance. Backed by competitive warranty coverage, ACDelco Pads give you the quality your vehicle deserves.

Features & Benefits:

- Friction material is integrally-molded to the backing plate for bond
- Premium shims, slots, and chamfers help to diminish noise, vibration, and braking harshness
- GM-recommended replacement part for your GM vehicle's original factory component
- · Manufactured to GM OE specification for fit, form, and function

Attention California Customers - WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

| Friction Material Thickness Inner Pad (IN) | .39 |
|--|--------|
| Friction Material Thickness Outer Pad (IN) | .39 |
| Friction Material Thickness Inner Pad (MM) | 9.91 |
| Friction Material Thickness Outer Pad (MM) | 9.91 |
| Friction Material Bonding Type | Bonded |
| Pad Shims Included | Yes |
| Pad Wear Sensor Included | Yes |

Alternate/OEM Part Number(s): 1711133, 22976409, 23441307

Warranty Information: 24 Month / Unlimited Mile Limited Warranty Details